

Model No. 4-Pole cage motor 6RN 315M 132kW D400V 50Hz IM3011-FF600

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	132	175	240	1488	847,2	IE1	95,4	95,5	95,1	0,85	0,82	0,74	7,22	2,46	2,71
690	Y				139												
460	D	60	152	203,8	235	1786	812,8	IE1	95,4	95,5	95,0	0,86	0,84	0,77	7,08	2,37	2,60

Motor type	6RN315M04E12
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	132 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. H
Temperature rise winding	79 K
Temperature rise surface	35 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0332 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	246%	704%	206%	271%	78,9 A
@ D 460V 60Hz	237%	697%	195%	260%	69,2 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF600
Cooling method	IC411
Motor weight - approx.	870 kg
Gross weight - approx.	900 kg
Motor inertia	2,2000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	76 dB(A)

Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000018049
P000018159



Driving efficiency and sustainability

