

**Model No.** 6-Pole cage motor 6RN 315M 90kW D400V 50Hz IM2021-FF600

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 400      | D             | 50        | 90        | 120       | 164      | 988        | 869,9     | IE2         | 93,7 94,2 94,0                     | 0,84 0,81 0,71                  | 7,01                                   | 2,37                                   | 2,82                                   |
| 690      | Y             |           |           |           | 95,3     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 460      | D             | 60        | 90        | 120       | 143      | 1190       | 722,3     | IE2         | 94,5 94,6 93,9                     | 0,83 0,79 0,69                  | 7,92                                   | 2,73                                   | 3,13                                   |

|                |                              |
|----------------|------------------------------|
| Motor type     | 6RN315M06E22                 |
| Enclosure      | Totally Enclosed Fan Cooling |
| Frame Material | Cast iron                    |
| Frame size     | 315M                         |
| Duty           | S1                           |
| Voltage        | 400 V                        |
| Frequency      | 50 Hz                        |
| Power output   | 90 kW                        |

|                               |                  |
|-------------------------------|------------------|
| Insulation class              | F                |
| Ambient temperature           | -20 till 40 °C   |
| Temperature rise              | temp.rise acc. B |
| Temperature rise winding      | 77 K             |
| Temperature rise surface      | 44 K             |
| Altitude above sea level      | 1000 mtr         |
| Hazardous area classification | Safe area        |

|                    |              |
|--------------------|--------------|
| Rotor type         | Cage motor   |
| Bearing type       | 6319/C3      |
| Lubrication method | 40gr/6000hrs |
| Type of grease     | Unirex N3    |

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 0,0598 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque<br>[% nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 237%                              | 701%                           | 229%                         | 282%                           | 56,6 A                    |
| @ D 460V 60Hz | 273%                              | 790%                           | 230%                         | 313%                           | 50,8 A                    |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM2021-FF600            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 730 kg                  |
| Gross weight - approx.             | 750 kg                  |
| Motor inertia                      | 2,5000 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 61 dB(A)                |

Direction of rotation cw /ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000014623

P000014624



Driving efficiency and sustainability

