

Model No. 8-Pole cage motor 6RN 315M 75kW D400V 50Hz IM1041

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	75	100	143	738	970,5	IE2	93,5 94,4 94,5	0,81 0,77 0,68	5,80	2,20	2,60
690	Y				82,5								
460	D	60	90	120	147	888	967,9	IE2	93,6 94,5 94,7	0,82 0,79 0,71	5,60	2,10	2,40

Motor type	6RN315M08E22
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	75 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Country of origin	CZ
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	220%	579%		260%	
@ D 460V 60Hz	210%	559%		240%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1041
Cooling method	IC411
Motor weight - approx.	1090 kg
Gross weight - approx.	1120 kg
Motor inertia	2,5000 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	61 dB(A)

Direction of rotation	cw / ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000014918
 P000014917



Driving efficiency and sustainability

