

Model No. 2-Pole cage motor 6RN 80M 0,75kW D230V 50Hz IM1081

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	0,75	1	2,9	2805	2,6	IE2	76,6	0,85	4,88	1,89	2,30
400	Y				1,67								
265	D	60	0,86	1,153	2,86	3410	2,4	IE2	78,5	0,84	5,21	1,85	2,23
460	Y				1,65								

Motor type	6RN80M02E22
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	80M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	0,75 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	62 K
Temperature rise surface	21 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM1081
Cooling method	IC411
Motor weight - approx.	09 kg
Gross weight - approx.	09 kg
Motor inertia	0,0001 kgm ²
Vibration level	according IEC60034-14

Rotor type	Cage motor
Bearing type	6004-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Country of origin	CZ
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	189%	486%		230%	1,46 A
@ D 265V 60Hz	185%	524%		223%	1,65 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000016074
P000016075



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

