

Model No. 4-Pole cage motor 6RN 80M 1,1kW D230V 50Hz IM2181-FT130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	1,1	1 1/2	4,6	1420	7,4	IE1	77,0	0,77	6,00	2,10	2,80
400	Y				2,65								
265	D	60	1,27	1,702	4,3	1670	7,3	N/A	79,0	0,81	4,50	2,40	2,50
460	Y				2,5								

Motor type	6RN80M04E16
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	80M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,1 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	76 K
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM2181-FT130
Cooling method	IC411
Motor weight - approx.	13 kg
Gross weight - approx.	13 kg

Vibration level according IEC60034-14

Direction of rotation cw /ccw

Rotor type	Cage motor
Bearing type	6004-2Z/C3WT

Type of grease Unirex N3

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	210%	600%		280%	2,66 A
@ D 265V 60Hz	240%	448%		250%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000042234
P000048131



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

