

**Model No.** 4-Pole cage motor 6RN 80M 1,1kW D230V 50Hz IM1081

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 1,1       | 1 1/2     | 4,35     | 1440       | 7,3       | IE2         | 81,4                               | 0,78                            | 6,10                                   | 2,40                                   | 3,00                                   |
| 400      | Y             |           |           |           | 2,5      |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 265      | D             | 60        | 1,27      | 1,702     | 4,25     | 1740       | 7,0       | IE2         | 84,0                               | 0,76                            |                                        |                                        |                                        |
| 460      | Y             |           |           |           | 2,45     |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN80M04E26                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Aluminum                     |
| Frame size                    | 80M                          |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 1,1 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise winding      | 40 K                         |
| Temperature rise surface      | 32 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM1081                  |
| Cooling method         | IC411                   |
| Motor weight - approx. | 11 kg                   |
| Gross weight - approx. | 11 kg                   |
| Motor inertia          | 0,0029 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6004-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|


|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 230V 50Hz | 240%                              | 609%                           | 212%                         | 300%                           | 2,46 A                    |
| @ D 265V 60Hz |                                   |                                |                              |                                |                           |

**NOTE**  
All performance values at rated voltage and frequency.  
All performance parameters are subjected to standard tolerance as per IEC 60034-1  
Voltage, Frequency are as per IEC60034-1  
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.



P000040909  
P000040910



Driving efficiency and sustainability

