

Model No. 2-Pole cage motor 6RN 90L 2,2kW D254V 60Hz IM3641-FT115

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 254      | D             | 60        | 2,2       | 3         | 6,4      | 3515       | 6,0       | IE3         | 86,5 86,5 85,5                     | 0,88                            | 7,79                                   | 4,00                                   | 2,45                                   |
| 440      | Y             |           |           |           | 3,7      |            |           |             |                                    |                                 |                                        |                                        |                                        |
|          |               |           |           |           |          |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN90L02E34                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Aluminum                     |
| Frame size                    | 90L                          |
| Duty                          | S1                           |
| Voltage                       | 254 V                        |
| Frequency                     | 60 Hz                        |
| Power output                  | 2,2 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6004-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                   |    |
|-------------------|----|
| Country of origin | CZ |
|-------------------|----|

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 254V 60Hz | 400%                              | 778%                           | 245%                         | 245%                           |                           |
|               |                                   |                                |                              |                                |                           |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3641-FT115            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 20 kg                   |
| Gross weight - approx.             | 21 kg                   |
| Motor inertia                      | 0,0021 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 69 dB(A)                |

|                       |         |
|-----------------------|---------|
| Direction of rotation | cw /ccw |
|-----------------------|---------|

Schematic presentation of torque-speed curve



P000046401



Driving efficiency and sustainability

