

Model No. 4-Pole cage motor 6RN 90L 1,5kW D230V 50Hz IM3641-FT130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	1,5	2	6,06	1415	10,1	IE1	76,3 76,9 73,9	0,80 0,72 0,57	4,73	2,35	2,56
400	Y				3,5								
265	D	60	1,75	2 1/3	5,92	1710	9,8	IE1	78,7 79,0 76,4	0,81 0,73 0,60	5,50	2,52	2,77
460	Y				3,42								

Motor type	6RN90L04E14
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	90L
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. H
Temperature rise winding	84 K
Temperature rise surface	49 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM3641-FT130
Cooling method	IC411
Motor weight - approx.	16 kg
Gross weight - approx.	16 kg
Motor inertia	0,0033 kgm ²
Vibration level	according IEC60034-14
Noise level (pressure) acc 60034-9	51 dB(A)

Rotor type	Cage motor
Bearing type	6004-2Z/C3WT

Type of grease	Unirex N3
----------------	-----------

Phase resistance at 20°C	5,0290 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	235%	475%	198%	256%	4,1 A
@ D 265V 60Hz	252%	550%	214%	277%	3,64 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000040873
P000040874



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

