

Model No. 4-Pole cage motor 6RN 90 2,2kW D230V 50Hz IM3641-FT130

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	2,2	3	8,7	1445	14,5	IE3	86,9 87,7 87,2	0,73 0,67 0,56	7,90	3,80	4,20
400	Y				5								
265	D	60	2,2	3	7,7	1770	11,9	IE2	87,0	0,72	9,00	3,70	4,10
460	Y				4,47								

Motor type	6RN90L04E36
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Aluminum
Frame size	90
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	2,2 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	37 K
Temperature rise surface	30 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Te time	0 sec

Degree of protection	IP55
Mounting type	IM3641-FT130
Cooling method	IC411
Motor weight - approx.	27 kg
Gross weight - approx.	28 kg

Vibration level according IEC60034-14

Direction of rotation cw / ccw

Rotor type	Cage motor
Bearing type	6004-2Z/C3WT

Type of grease Unirex N3

Phase resistance at 20°C	1,9183 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	380%	789%		420%	3,7 A
@ D 265V 60Hz	370%	896%		410%	2,54 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Schematic presentation of torque-speed curve



P000059393
P000063296



Driving efficiency and sustainability

