

**Model No.** 6-Pole cage motor 6RN 90S 0,75kW D230V 50Hz IM3041-FF165

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load<br>FL 3/4FL 1/2FL | PF at __ load<br>FL 3/4FL 1/2FL | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------------------------|---------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
| 230      | D             | 50        | 0,75      | 1         | 3,9      | 940        | 7,6       | IE1         | 71,1 70,3 65,5                     | 0,67 0,57 0,44                  | 3,66                                   | 1,80                                   | 2,27                                   |
| 400      | Y             |           |           |           | 2,25     |            |           |             |                                    |                                 |                                        |                                        |                                        |
| 265      | D             | 60        | 0,86      | 1,153     | 3,76     | 1140       | 7,2       | IE1         | 74,8 74,2 70,1                     | 0,66 0,57 0,44                  | 4,10                                   | 1,88                                   | 2,46                                   |
| 460      | Y             |           |           |           | 2        |            |           |             |                                    |                                 |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | 6RN90S06E10                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Aluminum                     |
| Frame size                    | 90S                          |
| Duty                          | S1                           |
| Voltage                       | 230 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 0,75 kW                      |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | temp.rise acc. B             |
| Temperature rise winding      | 67 K                         |
| Temperature rise surface      | 40 K                         |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Te time                       | 0 sec                        |

|                                    |                         |
|------------------------------------|-------------------------|
| Degree of protection               | IP55                    |
| Mounting type                      | IM3041-FF165            |
| Cooling method                     | IC411                   |
| Motor weight - approx.             | 14 kg                   |
| Gross weight - approx.             | 14 kg                   |
| Motor inertia                      | 0,0033 kgm <sup>2</sup> |
| Vibration level                    | according IEC60034-14   |
| Noise level (pressure) acc 60034-9 | 48 dB(A)                |

|              |              |
|--------------|--------------|
| Rotor type   | Cage motor   |
| Bearing type | 6004-2Z/C3WT |

|                |           |
|----------------|-----------|
| Type of grease | Unirex N3 |
|----------------|-----------|

|                          |            |
|--------------------------|------------|
| Phase resistance at 20°C | 3,7542 Ohm |
| Country of origin        | CZ         |

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 230V 50Hz | 180%                              | 364%                           |                              | 227%                           | 3,1 A                     |
| @ D 265V 60Hz | 188%                              | 409%                           |                              | 246%                           | 2,82 A                    |

### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

Schematic presentation of torque-speed curve



P000040875  
P000040876



Driving efficiency and sustainability

