

Model No. 2-Pole cage motor 6RN 90L 2,2kW D230V 50Hz IM3641-FT115

Table with 12 columns: U (V), Δ/Y Conn, f [Hz], P [kW], P [hp], I [A], n [RPM], T [Nm], IE Class, % EFF at \_\_ load (FL, 3/4FL, 1/2FL), PF at \_\_ load (FL, 3/4FL, 1/2FL), IA/IN [pu], TA/TN [pu], TK/TN [pu].

Table with 2 columns: Parameter and Value. Parameters include Motor type (6RNG90L02E34), Enclosure (Totally Enclosed Fan Cooling), Frame Material (Aluminum), Frame size (90L), Duty (S1), Voltage (230 V), Frequency (50 Hz), Power output (2,2 kW), Insulation class (F), Ambient temperature (-20 till 40 °C), Temperature rise (temp.rise acc. B (80K)), Temperature rise winding (38 K), Temperature rise surface (20 K), Altitude above sea level (1000 mtr), Hazardous area classification (Safe area), Degree of protection (IP55), Mounting type (IM3641-FT115), Cooling method (IC411), Motor weight - approx. (31 kg), Gross weight - approx. (32 kg), Motor inertia (0,0021 kgm²), Vibration level (according IEC60034-14), Direction of rotation (cw /ccw).

Table with 2 columns: Parameter and Value. Parameters include Rotor type (Cage motor), Bearing type (6004-2Z/C3WT).

Table with 2 columns: Parameter and Value. Parameter: Type of grease (Unirex N3).

Table with 2 columns: Parameter and Value. Parameter: Country of origin (CZ).

Table with 6 columns: Voltage/Freq, Locked rotor Torque [% nom], Starting current [% nom], Pull-up Torque [% nom], Breakdown Torque [% nom], No-load Current [A].

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Table with 3 columns: Efficiency, Europe, Global IEC. Standards: EN-IEC: 60034-30, IEC: 60034-30.

This is an uncontrolled copy, data can be changed anytime.

