

Model No. 6-Pole cage motor 7RN 315L 200kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	200	268,1	365	992	1925,4	IE3	96,4	95,9	95,6	0,82	0,77	0,67	8,09	2,85	3,11
690	Y				212												
460	D	60	200	268,1	325	1194	1599,7	IE3	96,8	95,8	95,3	0,81	0,76	0,65	9,32	3,10	3,50

Motor type	7RN315L06E37
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	200 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. B
Temperature rise winding	61 K
Temperature rise surface	38 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C4
Lubrication method	40gr/6000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0162 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	285%	808%		311%	149 A
@ D 460V 60Hz	310%	898%	280%	350%	134 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.


Degree of protection	IP55
Mounting type	IM1001
Cooling method	IC411
Motor weight - approx.	1770 kg
Gross weight - approx.	1820 kg
Motor inertia	6,2800 kgm ²

Vibration level according IEC60034-14

Direction of rotation cw / ccw

PTC 150°C

Schematic presentation of torque-speed curve



P000043354
P000043355



Driving efficiency and sustainability

