

Model No. 4-Pole cage motor 7RN 355L 500kW D400V 50Hz IM2021-FF840

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	500	670	870	1491	3202,5	IE3	96,9	0,86	8,56	3,03	3,25
690	Y				503								
460	D	60	500	670	760	1792	2664,6	IE3	97,1 97,1 96,7	0,85 0,81 0,72	9,92	3,46	3,64

Motor type	7RN355L04E35
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	355L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	500 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	81 K
Temperature rise surface	42 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6320/C4
Lubrication method	60gr/6000hrs
Type of grease	Unirex N3

Phase resistance at 20°C	0,0044 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	303%	855%	222%	325%	307 A
@ D 460V 60Hz	346%	990%	247%	364%	264 A

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2021-FF840
Cooling method	IC411
Motor weight - approx.	2290 kg
Gross weight - approx.	2360 kg
Motor inertia	8,3600 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000043156
P000052754



Driving efficiency and sustainability

