

Model No. 2-Pole cage motor QCA 132S 7,5kW D400V 50Hz IM2001-FF265

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	7,5	10	13,3	2943	24,3	IE4	91,7	91,7	90,3	0,89	0,84	0,75	8,80	3,10	4,30
690	Y				7,67												
460	D	60	8,6	11,53	11,7	3542	23,2	IE4	91,7	91,7	91,1	0,89	0,87	0,78	9,30	3,20	4,50

Motor type	QCA132SB2E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	7,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM2001-FF265
Cooling method	IC411
Motor weight - approx.	89 kg
Gross weight - approx.	92 kg

Vibration level according IEC60034-14

Direction of rotation cw /ccw

PTC 150°C

Rotor type	Cage motor
Bearing type	6208-2Z/C3

Type of grease Chevron SRI-2

Country of origin CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	310%	879%		430%	
@ D 460V 60Hz	320%	931%		450%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000054332

P000054333



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

