

Model No. 6-Pole cage motor QCA 180L 15kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	15	20	30,9	987	145,1	IE4	92,9	92,9	90,6	0,75	0,68	0,54	7,80	2,90	3,50
690	Y				17,8												
460	D	60	17,3	23,19	30,8	1186	139,3	N/A	91,7	91,7	90,9	0,77			7,80	2,80	3,40

Motor type	QCA180LA6E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	180L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	15 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM1001
Cooling method	IC411
Motor weight - approx.	270 kg
Gross weight - approx.	280 kg
Motor inertia	0,4279 kgm²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Rotor type	Cage motor
Bearing type	6211-2Z/C3WT
Type of grease	Chevron SRI-2

Country of origin	CN
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	290%	779%		350%	
@ D 460V 60Hz	280%	779%		340%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000049462
P000054555



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

