

**Model No.** 4-Pole cage motor QCA 200L 30kW D400V 50Hz IM1011

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |       |       | PF at __ load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
|          |               |           |           |           |          |            |           |             | FL               | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL |                                        |                                        |                                        |
| 400      | D             | 50        | 30        | 40        | 55,5     | 1485       | 192,9     | IE4         | 94,9             | 94,9  | 94,1  | 0,82          | 0,76  | 0,64  | 9,20                                   | 3,30                                   | 4,10                                   |
| 690      | Y             |           |           |           | 32,1     |            |           |             |                  |       |       |               |       |       |                                        |                                        |                                        |
| 460      | D             | 60        | 34,5      | 46,25     | 55,3     | 1787       | 184,4     | IE3         | 94,1             | 94,1  | 93,8  | 0,83          |       |       | 9,30                                   | 3,30                                   | 3,90                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | QCA200LA4E4                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 200L                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 30 kW                        |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |
| Rotor type                    | Cage motor                   |
| Bearing type                  | 6212/C3                      |
| Lubrication method            | 20gr/5250hrs                 |
| Type of grease                | Chevron SRI-2                |

Country of origin CZ

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [%<br>nom] | Pull-up<br>Torque [%<br>nom] | Breakdown<br>Torque [%<br>nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|------------------------|
| @ D 400V 50Hz | 330%                              | 918%                           |                              | 410%                           |                        |
| @ D 460V 60Hz | 330%                              | 927%                           |                              | 390%                           |                        |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                         |
|------------------------|-------------------------|
| Degree of protection   | IP55                    |
| Mounting type          | IM1011                  |
| Cooling method         | IC411                   |
| Motor weight - approx. | 320 kg                  |
| Gross weight - approx. | 330 kg                  |
| Motor inertia          | 0,5982 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14   |
| Direction of rotation  | cw /ccw                 |
|                        | PTC 150°C               |

Schematic presentation of torque-speed curve



P000049447  
P000054510



Driving efficiency and sustainability

