

Model No. 4-Pole cage motor QCA 200L 30kW D400V 50Hz IM3021-FF350

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	30	40	55,5	1485	192,9	IE4	94,9	94,9	94,1	0,82	0,76	0,64	9,20	3,30	4,10
690	Y				32,1												
460	D	60	34,5	46,25	55,3	1787	184,4	IE3	94,1	94,1	93,8	0,83			9,30	3,30	3,90

Motor type	QCA200LA4E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	200L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	30 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area
Rotor type	Cage motor
Bearing type	6212/C3
Lubrication method	20gr/10500hrs
Type of grease	Chevron SRI-2

Country of origin CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	330%	918%		410%	
@ D 460V 60Hz	330%	927%		390%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3021-FF350
Cooling method	IC411
Motor weight - approx.	320 kg
Gross weight - approx.	330 kg
Motor inertia	0,5982 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw / ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000049447

P000054510



Driving efficiency and sustainability

