

Model No. 2-Pole cage motor QCA 355L 315kW D400V 50Hz IM2001-FF740

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
FL	3/4FL	1/2FL	FL	3/4FL	1/2FL												
400	D	50	315	425	538	2989	1006,4	IE4	96,5	96,5	95,0	0,88			9,10	3,00	4,30
690	Y				310												
460	D	60	353	473,2	522	3588	939,6	IE4	96,2	96,2	95,1	0,88			9,40	3,10	4,20

Motor type	QCA355LB2E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	355L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	315 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6317/C3
Lubrication method	30gr/2500hrs
Type of grease	Chevron SRI-2

Country of origin CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	300%	908%		430%	
@ D 460V 60Hz	310%	940%		420%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2001-FF740
Cooling method	IC411
Motor weight - approx.	2140 kg
Gross weight - approx.	2200 kg
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000054419

P000054418



Driving efficiency and sustainability

