

**Model No.** 6-Pole cage motor QCA 355L 250kW D400V 50Hz IM1001

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |      |      | PF at __ load |      |      | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|------|------|---------------|------|------|----------------------------------------|----------------------------------------|----------------------------------------|
| FL       | 3/4FL         | 1/2FL     | FL        | 3/4FL     | 1/2FL    |            |           |             |                  |      |      |               |      |      |                                        |                                        |                                        |
| 400      | D             | 50        | 250       | 335       | 450      | 993        | 2404,3    | IE4         | 96,5             | 96,5 | 95,7 | 0,83          | 0,79 | 0,68 | 7,30                                   | 2,40                                   | 3,00                                   |
| 690      | Y             |           |           |           | 300      |            |           |             |                  |      |      |               |      |      |                                        |                                        |                                        |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | QCA355LB6E4                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 355L                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 250 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                    |               |
|--------------------|---------------|
| Rotor type         | Cage motor    |
| Bearing type       | 6322/C3       |
| Lubrication method | 60gr/11300hrs |
| Type of grease     | Chevron SRI-2 |

Country of origin CN

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current<br>[% nom] | Pull-up<br>Torque<br>[% nom] | Breakdown<br>Torque<br>[% nom] | No-load<br>Current<br>[A] |
|---------------|-----------------------------------|--------------------------------|------------------------------|--------------------------------|---------------------------|
| @ D 400V 50Hz | 240%                              | 728%                           |                              | 300%                           |                           |
|               |                                   |                                |                              |                                |                           |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                       |
|------------------------|-----------------------|
| Degree of protection   | IP55                  |
| Mounting type          | IM1001                |
| Cooling method         | IC411                 |
| Motor weight - approx. | 2180 kg               |
| Gross weight - approx. | 2250 kg               |
| Vibration level        | according IEC60034-14 |
| Direction of rotation  | cw /ccw               |
|                        | PTC 150°C             |

Schematic presentation of torque-speed curve



P000054620



Driving efficiency and sustainability

