

**Model No.** 6-Pole cage motor QCA 355M 200kW D400V 50Hz IM3011-FF740

| U<br>(V) | Δ / Y<br>Conn | f<br>[Hz] | P<br>[kW] | P<br>[hp] | I<br>[A] | n<br>[RPM] | T<br>[Nm] | IE<br>Class | % EFF at __ load |       |       | PF at __ load |       |       | I <sub>A</sub> /I <sub>N</sub><br>[pu] | T <sub>A</sub> /T <sub>N</sub><br>[pu] | T <sub>K</sub> /T <sub>N</sub><br>[pu] |
|----------|---------------|-----------|-----------|-----------|----------|------------|-----------|-------------|------------------|-------|-------|---------------|-------|-------|----------------------------------------|----------------------------------------|----------------------------------------|
|          |               |           |           |           |          |            |           |             | FL               | 3/4FL | 1/2FL | FL            | 3/4FL | 1/2FL |                                        |                                        |                                        |
| 400      | D             | 50        | 200       | 268,1     | 365      | 992        | 1925,4    | IE4         | 96,3             | 96,3  | 95,7  | 0,82          | 0,78  | 0,67  | 6,82                                   | 2,20                                   | 2,90                                   |
| 690      | Y             |           |           |           | 209      |            |           |             |                  |       |       |               |       |       |                                        |                                        |                                        |
| 460      | D             | 60        | 230       | 308,3     | 361      | 1192       | 1842,7    | IE3         | 96,3             | 95,8  | 95,4  | 0,83          | 0,82  | 0,72  | 6,90                                   | 2,20                                   | 2,90                                   |

|                               |                              |
|-------------------------------|------------------------------|
| Motor type                    | QCA355MB6E4                  |
| Enclosure                     | Totally Enclosed Fan Cooling |
| Frame Material                | Cast iron                    |
| Frame size                    | 355M                         |
| Duty                          | S1                           |
| Voltage                       | 400 V                        |
| Frequency                     | 50 Hz                        |
| Power output                  | 200 kW                       |
| Insulation class              | F                            |
| Ambient temperature           | -20 till 40 °C               |
| Temperature rise              | -                            |
| Temperature rise surface      |                              |
| Altitude above sea level      | 1000 mtr                     |
| Hazardous area classification | Safe area                    |

|                    |               |
|--------------------|---------------|
| Rotor type         | Cage motor    |
| Bearing type       | 6322/C3       |
| Lubrication method | 60gr/5650hrs  |
| Type of grease     | Chevron SRI-2 |

Country of origin CN

| Voltage/Freq  | Locked rotor<br>Torque [%<br>nom] | Starting<br>current [% nom] | Pull-up<br>Torque [% nom] | Breakdown<br>Torque [% nom] | No-load<br>Current [A] |
|---------------|-----------------------------------|-----------------------------|---------------------------|-----------------------------|------------------------|
| @ D 400V 50Hz | 220%                              | 682%                        |                           | 290%                        |                        |
| @ D 460V 60Hz | 220%                              | 689%                        |                           | 290%                        |                        |

#### NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

|            |                  |               |
|------------|------------------|---------------|
| Efficiency | Europe           | Global IEC    |
| Standards  | EN-IEC: 60034-30 | IEC: 60034-30 |

This is an uncontrolled copy, data can be changed anytime.

|                        |                          |
|------------------------|--------------------------|
| Degree of protection   | IP55                     |
| Mounting type          | IM3011-FF740             |
| Cooling method         | IC411                    |
| Motor weight - approx. | 1870 kg                  |
| Gross weight - approx. | 1930 kg                  |
| Motor inertia          | 11,5959 kgm <sup>2</sup> |
| Vibration level        | according IEC60034-14    |
| Direction of rotation  | cw /ccw                  |
|                        | PTC 150°C                |

Schematic presentation of torque-speed curve



P000049475  
P000054618



Driving efficiency and sustainability

