

Model No. 2-Pole cage motor QCA 80M 0,75kW D230V 50Hz IM2101-FT100

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
230	D	50	0,75	1	2,68	2885	2,5	IE4	83,5	83,5	80,6	0,84	0,78	0,66	7,20	3,50	3,90
400	Y				1,55												
265	D	60	0,86	1,153	2,7	3480	2,4	IE4	82,5	82,5	81,4	0,84	0,80	0,70	8,00	3,80	3,80
460	Y				1,56												

Motor type	QCA80MA2E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	80M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	0,75 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6204-2Z/C3WT

Type of grease	Chevron SRI-2
----------------	---------------

Country of origin	CN
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	350%	716%		390%	
@ D 265V 60Hz	380%	803%		380%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2101-FT100
Cooling method	IC411
Motor weight - approx.	21 kg
Gross weight - approx.	22 kg
Motor inertia	0,0016 kgm ²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000049393
P000054320



Driving efficiency and sustainability

