

Model No. 4-Pole cage motor QCA 90L 1,5kW D230V 50Hz IM3611-FT115

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
230	D	50	1,5	2	5,84	1457	9,8	IE4	88,2	88,2	84,8	0,73	0,64	0,49	8,10	3,80	4,20
400	Y				3,37												
265	D	60	1,7	2,279	5,7	1755	9,3	IE4	88,5	88,5	86,6	0,73			9,10	4,10	4,70
460	Y				3,3												

Motor type	QCA90L4E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	90L
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM3611-FT115
Cooling method	IC411
Motor weight - approx.	33 kg
Gross weight - approx.	34 kg

Vibration level **according IEC60034-14**

Direction of rotation **cw / ccw**

PTC 150°C

Rotor type	Cage motor
Bearing type	6205-2Z/C3WT

Type of grease **Chevron SRI-2**

Country of origin **CN**

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	380%	809%		420%	
@ D 265V 60Hz	410%	910%		470%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000054035

P000054447



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

