

Model No. 4-Pole cage motor QCA 90S 1,1kW D230V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
230	D	50	1,1	1 1/2	4,1	1447	7,3	IE4	87,2	87,2	82,1	0,77			7,10	3,00	3,60
400	Y				2,37												
265	D	60	1,27	1,702	4,12	1745	7,0	IE4	87,5	87,5	86,2	0,77			8,00	3,20	3,90
460	Y				2,38												

Motor type	QCA90S4E4
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	90S
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	1,1 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM1001
Cooling method	IC411
Motor weight - approx.	30 kg
Gross weight - approx.	31 kg
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Rotor type	Cage motor
Bearing type	6205-2Z/C3WT
Type of grease	Chevron SRI-2

Country of origin	CN
-------------------	----

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	300%	709%		360%	
@ D 265V 60Hz	320%	800%		390%	

NOTE


All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30



P000054423

P000054424



This is an uncontrolled copy, data can be changed anytime.

Driving efficiency and sustainability

