

Model No. 4-Pole cage motor TCA 132M 7,5kW D230V 50Hz IM2001-FF265

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
230	D	50	7,5	10	24,9	1462	49,0	IE3	89,7	0,83	6,77	2,10	2,65
400	Y				14,4								
265	D	60	8,6	11,53	24,7	1760	46,7	IE2	89,5	0,85	6,83	2,21	2,55
460	Y				14,2								

Motor type	TCA132M4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132M
Duty	S1
Voltage	230 V
Frequency	50 Hz
Power output	7,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	67 K
Temperature rise surface	46 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Degree of protection	IP55
Mounting type	IM2001-FF265
Cooling method	IC411
Motor weight - approx.	93 kg
Gross weight - approx.	96 kg
Motor inertia	0,0550 kgm²
Vibration level	according IEC60034-14

Rotor type	Cage motor
Bearing type	6208-2Z/C3

Type of grease	Chevron SRI-2
----------------	----------------------

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 230V 50Hz	210%	678%		265%	9,39 A
@ D 265V 60Hz	221%	680%		255%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Schematic presentation of torque-speed curve



P000043429
P000044105



Driving efficiency and sustainability

