

Model No. 4-Pole cage motor TCA 132M 7,5kW D400V 50Hz IM3001-FF265

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL			PF at __load FL 3/4FL 1/2FL			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	7,5	10	14,4	1465	48,9	IE3	90,4			0,83			7,50	2,80	3,00
690	Y				8,4												
460	D	60	8,6	11,53	14,4	1760	46,7	IE2	89,5		89,5	0,84			7,69	2,81	3,00

Motor type	TCA132M4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	7,5 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6208-2Z/C3

Type of grease	Chevron SRI-2
----------------	----------------------

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	280%	750%		300%	
@ D 460V 60Hz	281%	763%		300%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3001-FF265
Cooling method	IC411
Motor weight - approx.	80 kg
Gross weight - approx.	82 kg
Motor inertia	0,0550 kgm²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000064442
P000019582



Driving efficiency and sustainability

