

Model No. 2-Pole cage motor TCA 132S 7,5kW D400V 50Hz IM3611-FT165

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	7,5	10	13,3	2934	24,4	IE3	90,1	90,1	89,3	0,90	0,87	0,78	7,80	2,60	3,60
690	Y				7,8												
460	D	60	8,6	11,53	13,2	3533	23,2	IE2	90,2	90,2	89,9	0,91	0,89	0,81	8,20	2,66	3,70
					7,7												

Motor type	TCA132SB2E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	132S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	7,5 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	57 K
Temperature rise surface	34 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6208-2Z/C3

Type of grease	Chevron SRI-2
----------------	----------------------

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	260%	774%		360%	4,26 A
@ D 460V 60Hz	266%	818%		370%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3611-FT165
Cooling method	IC411
Motor weight - approx.	78 kg
Gross weight - approx.	80 kg
Motor inertia	0,0210 kgm²
Vibration level	according IEC60034-14

Direction of rotation	cw / ccw
-----------------------	-----------------

PTC 150°C

Schematic presentation of torque-speed curve



P000019597

P000019598



Driving efficiency and sustainability

