

Model No. 4-Pole cage motor TCA 180L 22kW D400V 50Hz IM2001-FF300

Table with 13 columns: U (V), Δ/Y Conn, f [Hz], P [kW], P [hp], I [A], n [RPM], T [Nm], IE Class, % EFF at __ load (FL, 3/4FL, 1/2FL), PF at __ load (FL, 3/4FL, 1/2FL), IA/IN [pu], TA/TN [pu], TK/TN [pu]. Rows show performance data for 400V and 460V configurations.

Table with 2 columns: Parameter and Value. Rows include Motor type (TCA180LA4E3), Enclosure (Totally Enclosed Fan Cooling), Frame Material (Cast iron), Frame size (180L), Duty (S1), Voltage (400 V), Frequency (50 Hz), Power output (22 kW), Insulation class (F), Ambient temperature (-20 till 40 °C), Temperature rise (65 K), Temperature rise winding (40 K), Altitude above sea level (1000 mtr), Hazardous area classification (Safe area), Degree of protection (IP55), Mounting type (IM2001-FF300), Cooling method (IC411), Motor weight (225 kg), Gross weight (232 kg), Motor inertia (0,2415 kgm²), Vibration level (according IEC60034-14), Direction of rotation (cw /ccw), PTC (150°C).

Table with 2 columns: Parameter and Value. Rows include Rotor type (Cage motor), Bearing type (6211-2Z/C3WT).


Table with 2 columns: Parameter and Value. Row includes Type of grease (Chevron SRI-2).

Table with 2 columns: Parameter and Value. Row includes Country of origin (CN).

Table with 6 columns: Voltage/Freq, Locked rotor Torque [% nom], Starting current [% nom], Pull-up Torque [% nom], Breakdown Torque [% nom], No-load Current [A]. Rows show data for @ D 400V 50Hz and @ D 460V 60Hz.

NOTE
All performance values at rated voltage and frequency.
All performance parameters are subjected to standard tolerance as per IEC 60034-1
Voltage, Frequency are as per IEC60034-1
Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Table with 3 columns: Parameter, Europe, Global IEC. Rows include Efficiency and Standards (EN-IEC: 60034-30, IEC: 60034-30).



This is an uncontrolled copy, data can be changed anytime.