

Model No. 4-Pole cage motor TCA 180L 22kW D400V 50Hz IM1011

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	22	30	41,6	1474	142,5	IE3	93,0	0,82	7,46	2,42	3,31
690	Y				24								
460	D	60	25,3	33,91	40,7	1774	136,2	IE3	93,6 93,6 92,7	0,83	7,66	2,70	3,50

Motor type	TCA180LA4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	180L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	22 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	65 K
Temperature rise surface	40 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6211-2Z/C3WT

Type of grease	Chevron SRI-2
----------------	----------------------

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	242%	745%		331%	16,6 A
@ D 460V 60Hz	270%	766%		350%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30


This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1011
Cooling method	IC411
Motor weight - approx.	196 kg
Gross weight - approx.	202 kg
Motor inertia	0,2415 kgm²
Vibration level	according IEC60034-14

Direction of rotation	cw /ccw
-----------------------	----------------

PTC 150°C

Schematic presentation of torque-speed curve



P000019624

P000019625



Driving efficiency and sustainability

