

Model No. 4-Pole cage motor TCA 200L 30kW D400V 50Hz IM2001-FF350

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	30	40	54	1482	193,3	IE3	93,6	94,0	93,5	0,86	0,82	0,73	7,98	2,20	2,90
690	Y				31,3												
460	D	60	34,5	46,25	54,1	1778	185,3	IE2	93,0	93,0	93,0	0,86			7,98	2,20	2,90

Motor type	TCA200LA4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	200L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	30 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	48 K
Temperature rise surface	32 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6212/C3
Lubrication method	20gr/10500hrs
Type of grease	Chevron SRI-2

Phase resistance at 20°C	0,2506 Ohm
Country of origin	CZ

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	220%	800%		290%	19,9 A
@ D 460V 60Hz	220%	798%		290%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2001-FF350
Cooling method	IC411
Motor weight - approx.	235 kg
Gross weight - approx.	242 kg
Motor inertia	0,4800 kgm²

Vibration level **according IEC60034-14**

Direction of rotation **cw / ccw**

PTC 150°C

Schematic presentation of torque-speed curve



P000019639

P000019640



Driving efficiency and sustainability

