

Model No. 4-Pole cage motor TCA 225S 37kW D400V 50Hz IM2001-FF400

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	37	49,6	67,2	1483	238,3	IE3	93,9	0,85	7,10	2,16	2,80
690	Y				38,8								
460	D	60	42,5	56,97	66,3	1783	227,6	IE2	93,6 93,6 93,6	0,86	7,35	2,40	3,10

Motor type	TCA225S4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	225S
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	37 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6213/C3
Lubrication method	22gr/10200hrs
Type of grease	Chevron SRI-2

Phase resistance at 20°C	0,1776 Ohm
Country of origin	CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	216%	709%		280%	25,3 A
@ D 460V 60Hz	240%	736%		310%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM2001-FF400
Cooling method	IC411
Motor weight - approx.	310 kg
Gross weight - approx.	320 kg
Motor inertia	0,6700 kgm²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000019665

P000019666



Driving efficiency and sustainability

