

Model No. 4-Pole cage motor TCA 280M 90kW D400V 50Hz IM1011

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	90	120	154	1489	577,2	IE3	95,6	95,6	94,8	0,88	0,85	0,78	6,07	2,03	2,38
690	Y				89,3												
460	D	60	104	139,4	158	1788	555,5	IE2	95,0			0,87			6,32	2,40	2,70

Motor type	TCA280MA4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	280M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	90 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	60 K
Temperature rise surface	36 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6317/C3
Lubrication method	30gr/8000hrs
Type of grease	Chevron SRI-2

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	203%	609%		238%	47,2 A
@ D 460V 60Hz	240%	632%		270%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30


This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1011
Cooling method	IC411
Motor weight - approx.	700 kg
Gross weight - approx.	720 kg
Motor inertia	4,5100 kgm²
Vibration level	according IEC60034-14

Direction of rotation	cw / ccw
-----------------------	-----------------

PTC 150°C

Schematic presentation of torque-speed curve



P000019685

P000019686



Driving efficiency and sustainability

