

Model No. 4-Pole cage motor TCA 315L 200kW D400V 50Hz IM3011-FF600

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load			PF at __ load			I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
									FL	3/4FL	1/2FL	FL	3/4FL	1/2FL			
400	D	50	200	268,1	344	1488	1283,6	IE3	96,1	96,3	96,0	0,89	0,86	0,79	7,24	2,80	3,30
690	Y				199												
460	D	60	230	308,3	340	1787	1229,2	IE2	95,4	95,4	95,2	0,89			7,32	2,80	3,30

Motor type	TCA315LC4E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	315L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	200 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	temp.rise acc. F
Temperature rise winding	69 K
Temperature rise surface	31 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6319/C3
Lubrication method	40gr/6000hrs
Type of grease	Chevron SRI-2

Phase resistance at 20°C	0,0189 Ohm
Country of origin	CN

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	280%	723%		330%	103 A
@ D 460V 60Hz	280%	732%		330%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF600
Cooling method	IC411
Motor weight - approx.	1200 kg
Gross weight - approx.	1240 kg

Vibration level	according IEC60034-14
-----------------	------------------------------

Direction of rotation	cw / ccw
-----------------------	-----------------

PTC 150°C

Schematic presentation of torque-speed curve



P000019711

P000019712



Driving efficiency and sustainability

