

Model No. 8-Pole cage motor TCA 355L 200kW D400V 50Hz IM3011-FF740

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	200	268,1	361	742	2574,1	IE3	94,6	0,85	6,33	1,58	2,36
690	Y				208								
460	D	60	230	308,3	356	892	2462,4	IE3	95,0	0,85	6,30	1,53	2,24
					205								

Motor type	TCA355LA8E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	355L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	200 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-

Temperature rise surface	
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6322/C3
Lubrication method	60gr/6950hrs
Type of grease	Chevron SRI-2

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	158%	631%		236%	124 A
@ D 460V 60Hz	153%	629%		224%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM3011-FF740
Cooling method	IC411
Motor weight - approx.	1870 kg
Gross weight - approx.	1930 kg
Motor inertia	1,5300 kgm²
Vibration level	according IEC60034-14

Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000019733
P000019734



Driving efficiency and sustainability

