

Model No. 2-Pole cage motor TCA 355L 315kW D400V 50Hz IM1001

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	315	425	527	2984	1008,1	IE3	95,8	0,90	7,00	2,10	3,30
690	Y				306								
460	D	60	353	473,2	513	3583	940,9	IE3	95,8 95,6 94,6	0,90	7,30	2,18	3,24
					294								

Motor type	TCA355LB2E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	355L
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	315 kW

Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	75 K
Temperature rise surface	41 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6317/C3
Lubrication method	30gr/2500hrs
Type of grease	Chevron SRI-2

Country of origin	CN
-------------------	-----------

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	210%	700%		330%	143 A
@ D 460V 60Hz	218%	729%		324%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1

Technical data are subject to change. There may be discrepancies between calculated and name plate values.


Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1001
Cooling method	IC411
Motor weight - approx.	1870 kg
Gross weight - approx.	1930 kg
Motor inertia	4,5200 kgm²
Vibration level	according IEC60034-14

Direction of rotation	cw / ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000019735
P000019736



Driving efficiency and sustainability

