

Model No. 6-Pole cage motor TCA 355M 160kW D400V 50Hz IM1011

U (V)	Δ / Y Conn	f [Hz]	P [kW]	P [hp]	I [A]	n [RPM]	T [Nm]	IE Class	% EFF at __ load FL 3/4FL 1/2FL	PF at __ load FL 3/4FL 1/2FL	I _A /I _N [pu]	T _A /T _N [pu]	T _K /T _N [pu]
400	D	50	160	214,5	286	992	1540,3	IE3	95,8	0,84	6,64	1,96	2,70
690	Y				165								
460	D	60	192	257,4	294	1191	1539,5	IE3	95,8 95,7 94,9	0,86	6,45	1,82	2,49
					169								

Motor type	TCA355MA6E3
Enclosure	Totally Enclosed Fan Cooling
Frame Material	Cast iron
Frame size	355M
Duty	S1
Voltage	400 V
Frequency	50 Hz
Power output	160 kW
Insulation class	F
Ambient temperature	-20 till 40 °C
Temperature rise	-
Temperature rise winding	58 K
Temperature rise surface	31 K
Altitude above sea level	1000 mtr
Hazardous area classification	Safe area

Rotor type	Cage motor
Bearing type	6322/C3
Lubrication method	60gr/5650hrs
Type of grease	Chevron SRI-2

Country of origin **CN**

Voltage/Freq	Locked rotor Torque [% nom]	Starting current [% nom]	Pull-up Torque [% nom]	Breakdown Torque [% nom]	No-load Current [A]
@ D 400V 50Hz	196%	664%		270%	97,6 A
@ D 460V 60Hz	182%	642%		249%	

NOTE

All performance values at rated voltage and frequency.

All performance parameters are subjected to standard tolerance as per IEC 60034-1

Voltage, Frequency are as per IEC60034-1


Technical data are subject to change. There may be discrepancies between calculated and name plate values.

Efficiency	Europe	Global IEC
Standards	EN-IEC: 60034-30	IEC: 60034-30

This is an uncontrolled copy, data can be changed anytime.

Degree of protection	IP55
Mounting type	IM1011
Cooling method	IC411
Motor weight - approx.	1570 kg
Gross weight - approx.	1620 kg
Motor inertia	9,6000 kgm²
Vibration level	according IEC60034-14
Direction of rotation	cw /ccw
	PTC 150°C

Schematic presentation of torque-speed curve



P000019753
P000019754



Driving efficiency and sustainability

